Polyform® F2Heavy Duty Fender

Product information



16 L

Proudly made by The Originator of Modern Plastic Buoys

POLYFORM® OF NORWAY

The POLYFORM® F2 is a supreme, seamless, heavy duty fender with an extra strong pre-made injection molded ropehold. The fender and the rib-reinforced ropehold are unified through the in-house and developed patented POLYMATIQ technology. The F-series are made from our unique blend of high class tough, flexible vinyl materials. The fenders are resistant to all weather conditions. The Fseries fenders are used all over the world for fendering of pleasure boats, yachts, workboats, pilot boats and the largest F-series fenders are used by national navies for ships up to 1500 ton d/w.

Available in various colours.

340 \$30 \$10 \$220

Article number	F2
Diameter (max recomended)	220 mm
Height (max)	610 mm
Weight (nominal)	1,75 Kg
Eye diameter for ropehold	28 mm
Valve type	V10

Technical information

Gross volume

i cerminear minorimation	
Breaking load for ropehold	1400 kp
Buoy body material description	
Hardness, shore A	66
Tensile strength	13,9 MPa
Elongation at break	587%
Cold flex temperature	-33°C
Recommended max temp.	40°C
Temp. not to be exceeded	50°C
Specific gravity	1,17
Body and Ropehold made from PVC.	
No use of CFC. Cadmium free.	

Made by Polymatic® production technology



Polyform AS

Polyform AS is a world leading manufacturer of buoys fenders and floats, and the originator of the modern inflatable plastic buoy. The company is registered in Norway and situated in Ålesund at the northwestern coast of Norway, and benefits from being located in one of the world's most innovative maritime environments.

The product range of Polyform AS consists of:

- •Inflatable buoys and fenders made from soft Vinyl plastics.
- Purse Seine Floats, buoys and marina fenders made from BACELL closed cell foam.
- Hard-shell buoys and pontoon floats made from PE and filled with foam

POLYFORM AS

Tverrvegen 37 N-6020 Ålesund Norway ★ +47 70 17 25 50
 ★ +47 70 14 76 36
 mail@polyform.no
 www.polyform.no

Stress (MPa) PVC Material

For all measurements, weights and other technical data specified in this data sheet, please allow for a deviation of not less than +/-5%. The illustration may deviate from the actual product.